

Revolutionary "Three Step" Terrazzo Resurfacing & Polishing Procedures



Step 1 & 2 Scratch Removal Discs (SRD's):

Thoroughly strip the floor to completely remove surface coatings i.e. floor finish, floor wax, acrylic sealers.

Hone the terrazzo floor with the 120 grit (black) SRD's mounted to a white pad, using the male-to-male velcro kit. Honing time 20-30 seconds per square feet with water.

Hone the terrazzo floor with the "Peach" color SRD's mounted to a white pad, using the male-to-male velcro kit. Repeating the same process in step one.

Honing time is 20-30 seconds per square feet. Work an area of 16-20 square feet at a time. Keep surface wet.

Vacuum the slurry with a commercial duty wet vacuum and rinse the floor with Neutral Stone Cleaner.



Parish Maintenance Supply
114 Palmetto St.
315-433-9031

Syracuse NY 13206
www.parish-Supply.com
315-433-9840 fax

Wet Polishing using "Stone Polish Paste" for Terrazzo Floors

Prior to polishing

"Thoroughly hone the floor with SRD's"

Protect surfaces that should not get wet. Work 20 sq. ft. at a time.

Polishing Procedures:

1. Thoroughly mix compound in the pail with a small scoop (1-2 ounce).
2. Apply 1 scoop to the floor in a circle, matching the diameter of the pad being used. Add 2-3 ounces of clean cool water to the compound.

Using a "Natural Fiber" polish pad and a 175 rpm floor machine quickly make one pass over an area of 20 sq. ft.

Continue to buff the compound for 15-30 seconds per sq. ft., working the machine in a crosshatch pattern. Keep the compound wet at all times, do not allow floor to dry.

If the slurry becomes too dry add small amounts of water as needed.

Use a high quality wet vacuum with a squeegee tool, remove the slurry residue.

Once all the wet slurry has been completely vacuumed, damp mop the floor surface with the Neutral Stone Floor Cleaner at a ratio of 2 ounces per gallon of water.



Repeat application if higher gloss is desired



Parish Maintenance Supply
114 Palmetto St.
315-433-9031

Syracuse NY 13206
www.parish-supply.com
315-433-9840 fax

Protect with **Stone Impregnating Sealer**

Impregnator H2O sealer is designed for the protection of all medium to dense porous stone surfaces.



Clean daily with **Neutral Stone Cleaner**

A Chelate-free cleaner, is the ideal neutral stone floor cleaner for all natural stone floors For daily cleaning dilute 1:64



Maintain gloss with **Twister Floor Pads**

Use the Twister floor pads to clean and polish your floors on a regular basis. Replace your ordinary pads with Twister System to maintain that High Gloss Shine.



Parish Maintenance Supply
114 Palmetto St.
315-433-9031

Syracuse NY 13206
www.parish-Supply.com
315-433-9840 fax