

Hygienic Green Cleaning Systems

Critical Disease Transfer Surfaces

ATP Demo Report

End-User Location: _____

Date: _____

Distributor Name: _____

| Kaivac No-Touch Cleaning™ | | | | | | |
|---------------------------|----------------------------|------------------|---------------|----------|------------|-----------|
| Cleaning Method | Area | Surface Material | Excellent ATP | Pass ATP | Before ATP | After ATP |
| KaiFly | Desktop | Formica | < 15 | < 30 | | |
| | Cafeteria Table | Formica | < 15 | < 30 | | |
| | Countertop | Formica | < 15 | < 30 | | |
| KaiVac | Toilet Seat | Plastic | < 15 | < 30 | | |
| | Toilet Floor (avoid grout) | Terrazo | < 20 | < 60 | | |
| | Soap Dispenser | Plastic | < 20 | < 60 | | |
| | Sink Handle | Chrome | | < 30 | | |
| | Wrestling Mat | | < 50 | < 100 | | |
| KaiWipes | Towel Disp Handle | Plastic | < 150 | < 300 | | |
| | Door Handle | Aluminum | < 150 | < 300 | | |
| | Keyboard/Mouse | | < 150 | < 300 | | |
| | Phone | Plastic | < 150 | < 300 | | |
| | Stair Railing | | < 150 | < 300 | | |

CAUTION: Keep swabs refrigerated when not in use. Avoid extreme temperatures, hot and cold. Extreme temperature exposure will significantly lower readings.

Quality Testing of Swabs (test batch of swabs immediately before demo):

1. To test quality of swabs, apply a drop of saliva to finger, wipe on tip of swab, and test.
2. Result should be greater than 2000. If low, open a new batch of swabs and retest.

ATP Measurement Technique:

1. Remove swabs from cooler (allow 10 minutes at room temperature).
2. Turn on meter (press red button) and allow for self-test and calibration (60 seconds).
3. After calibration is complete, remove fresh swab from tube. For flat surfaces outline a 4 x 4 inch area with the swab tip (if swab tip is dry discard and replace). Rub swab tip back and forth over the area. Rotate the swab as you rub. Repeat swabbing in the perpendicular direction. For other surfaces (door knobs, sink handles, etc), swab the entire surface and repeat same pattern each time.
4. Return swab into tube. Snap the end with the fluid both directions. Holding vertically, shake swab 3 times.
5. Open lid of meter and put in the swab, tip-end first. Close lid.
6. Holding the meter vertically, immediately press OK. Wait for reading. Record information.

Parish-Supply.com
 Syracuse, NY 315-433-9031
 www.parish-supply.com



| ATP Levels of Clean (RLU) | |
|---|----------|
| <p style="text-align: center;">Ultra-Clean</p> <p style="text-align: center;">Sterile surfaces and food prep areas</p> | 0-10 |
| <p style="text-align: center;">Very Clean</p> <p style="text-align: center;">Critical touch points</p> | 11-30 |
| <p style="text-align: center;">Good Clean</p> <p style="text-align: center;">Floor req'mt, and typical microfiber towel performance</p> | 31-80 |
| <p style="text-align: center;">Somewhat Dirty</p> <p style="text-align: center;">Caution: Surface should be cleaned and has some risk of contamination from disease-causing bacteria (typical mopping practices perform in this range)</p> | 81-200 |
| <p style="text-align: center;">Dirty</p> <p style="text-align: center;">Warning: Surface needs cleaning and has medium risk of contamination from disease-causing bacteria</p> | 201-500 |
| <p style="text-align: center;">Very Dirty</p> <p style="text-align: center;">Danger: Surface needs cleaning and has medium to high risk of contamination from disease-causing bacteria</p> | 501-1000 |
| <p style="text-align: center;">Filthy</p> <p style="text-align: center;">Danger: Surface needs cleaning and has high risk of contamination from disease-causing bacteria</p> | > 1000 |

