



## NewAge PowerPrep Cleaner Step 1 of Fast Coat System

This product is formulated specifically to prepare wood floors for recoating of water-based finishes. It deep cleans existing wood floor coatings by quickly and effectively penetrating and loosening embedded soils, body oils, and scuff marks. After a clean water rinse the floor is prepared for coating. This product is formulated specifically to prepare wood floors for the recoating of water-based finishes. For use on gym floors, racquetball courts, and sealed wood floors.

### TYPICAL PROPERTIES

Color .....	Straw
Detergency.....	Excellent
Emulsification.....	Excellent
Rinsability.....	Complete
Foam.....	Low
Fragrance... ..	Citrus
Freezing Point.....	< 32° F
pH.....	9.5
Solubility in water.....	Complete
Specific gravity.....	1.005
Weight per gallon.....	8.37 lbs.
Shelf life.. ..	1 year

### RECOMMENDED APPLICATION

**Read this entire label before using the product.**

*Fast Coat System Procedures:* To prepare the floor for the cleaning process, remove all dry soils, chewing gum, and other debris from the floor. Vacuum the dirt from the floor.

1. Dilute product at 4 oz. per gallon of clean water.
2. Apply using an auto scrubber with blue scrub pads or mop on solution in small sections of the floor. Allow a few minutes of dwell time and then scrub the area with use of an auto scrubber or low speed floor machine. Rotate blue pads at a rate of 800 sq.ft./pad. Double scrub area with an auto scrubber, IF NECESSARY. Inspect floor to see that all scuff marks are removed. Repeat cleaning process if necessary to remove additional soils and marks.
3. Rinse floor with clean water.
4. Allow the floor to dry completely before applying the appropriate bonding agent (step 2 in the Fast Coat System)

**Scrub and Recoat Procedure:**

Follow same procedures as described above for the Fast Coat System only use maroon top scrub pads at a rate of 400 sq.ft./pad. After floor has dried completely, a water-based wood floor coating can be applied following product label direction.

**Interim Cleaning:**

To use this product for removing heavy soils and black marks, dilute product 2 oz./gallon of clean water and scrub floor using a white or red pad. Rinse floor with clean water or wood floor maintenance cleaner following label directions.

**OBLIGATION OF MANUFACTURER**

The following is made in lieu of all warranties, expressed or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, the user shall determine the suitability of the product for the intended use and user assumes all risk and liability whatsoever in connection therewith. The foregoing may not be altered except by an agreement signed by officers of seller and manufacturer.