

## Revolutionary Two Step Terrazzo / Marble Resurface and Polishing Procedures

### Step 1 — Scratch Removal Discs (SRD's):

Thoroughly strip  
the floor to completely  
remove surface coatings.



Hone the marble  
with Foam Disc Holder  
& Scratch Removal  
Discs with water.



Honing process  
time is 30 seconds  
per square foot, 8 minutes  
For 16 square feet.  
Keep surface wet



Vacuum the slurry  
and rinse with  
Neutral Stone  
Cleaner.



### Wet Polishing for Terrazzo & Marble Floors (Maintenance Procedure)

#### Prior to polishing

**“Thoroughly strip the floor to completely remove surface coatings”**

Mix in a plastic container at a rate ratio of 1 ounce of Marble  
Polish Power to 4 ounces of water.

Pour the mixture directly onto the floor.

Do not allow product to dwell on floor surface without  
machine buffing / polishing.



Using a White or Light Natural Fiber floor pad and a 175 RPM floor machine, buff approximately 16-20 square feet with the mixture with a white polishing pad.

Continue to buff the mixture for 30 seconds per square foot.

Buff the floor at a rate of 8 minutes for 16 square feet.

Keep mixture wet at all times.



Use a high quality wet vacuum with a squeegee tool to remove the slurry residue.

Once all the wet slurry has been completely vacuumed, damp mop the floor surface with the Stone Floor Cleaner at a ratio of 2 ounces per gallon of water.



### Repeat application if higher gloss is desired

#### Protect with **Marble Impregnating Sealer**

Stone Impregnator sealer is designed for the protection of all medium to dense porous stone surfaces.



#### Clean daily with **Neutral Stone Cleaner**

A Chelate-free cleaner, fortified with impregnator technology to further protect the stone with each use. For daily cleaning dilute 1:64



#### Maintain gloss with **Marble Gloss Maintainer**

A liquid routine maintenance product for marble. Used to maintain wet look in high traffic areas.

