



Innovative Cleaning Systems
www.tornadovac.com

ELECTRIC JUMBO EXTERNAL FILTER WET/DRY VACUUMS



SINGLE ELECTRIC JUMBO
DUAL ELECTRIC JUMBO

ELECTRIC JUMBO EXTERNAL FILTER WET/DRY VACUUMS

High-speed bulk recovery, with 55-gallon steel drums for industrial applications

It is a simple principle: the higher the c.f.m. a vacuum generates, the better suited it is for recovering dry debris and bulk material. Tornado's electric powered jumbo vacuum systems are designed to face the rigors of industrial applications. The Single Electric Jumbo has a 2.25 HP powerhead mounted on a steel, rolled-top 55-gallon drum. An external poly bag is mounted on a support rod and serves as a final filter. The majority of the debris, including small particles, is actually recovered in the steel drum. The Dual Electric has an additional powerhead for added c.f.m. and two external poly filter bags.

Both the Single and the Dual Electric Jumbo comes standard with a drum and a four-wheeled steel dolly with convenient transport handle.

Electric Jumbo Vac Systems are appropriate for use in recovering heavy solid debris such as metal shavings and chips, sand, sawdust, and powder. The units are also effective in recovering water and cutting oil. A liquid shut-off float can be added to either unit. Attachment sets are required for operation and are sold separately.



95954 Single Electric Jumbo
Comes complete with 2.25 HP powerhead, drum, filter, and dolly. Tornado's Jumbo vac systems are tailored for the maintenance professional faced with the demands of industrial applications.



95960 Dual Electric Jumbo
Features an additional 2.25 HP powerhead and poly bag for recovery of heavier debris such as heavy machine oil and metal shavings and chips.



Rugged
The 55-gallon, rolled-top, ribbed steel drum is superior to plastic or stainless steel tanks for heavy duty applications. The drum also features an industrial gate valve for ease in emptying liquids.

CFM vs. Waterlift Many competitive vacuum systems use waterlift as the primary measure of effectiveness and power. In a heavy industrial application, however, such vacs may lack sufficient airflow (cubic feet per minute, or CFM) to meet requirements. A unit's CFM tells the true story of its capability in bulk recovery environments. With high-levels of airflow (up to 340 CFM on the Dual Jumbo), a Tornado Electric Jumbo Vac System is ideal for rapid, efficient high-volume debris recovery.

Mobile

Despite their size and power, Tornado Jumbo vacs are highly portable, thanks to a four-wheeled dolly, included standard.



ELECTRIC JUMBO WET/DRY APPLICATION GUIDE (★ = Excellent; ✓ = Good)

MODEL	CATALOG NUMBER	WATER	CUTTING OIL	MACHINE OIL	HEAVY MACHINE OIL	LIGHT SOLID DEBRIS	HEAVY SOLID DEBRIS	SAWDUST	POWDER	ULTRA FINE POWDER	SAND	OIL DRY	METAL SHAVINGS AND CHIPS
SE JUMBO	95954	✓	★	✓		★	✓	★	★	★	✓	✓	✓
DE JUMBO	95960	✓	★	★	✓	★	★	★	★	★	★	★	★

PRODUCT SPECIFICATIONS

MODEL	CATALOG NUMBER	2.25 POWERHEADS	STATIC WATERLIFT	CFM (ORIFICE)	POLY EXTERNAL FILTERS	FILTER AREA	EFFECTIVE HORIZONTAL REACH
SE JUMBO	95954	One	51"	184 (2')	One	1874 in ²	30'
DE JUMBO	95960	Two	51"	243 (2') / 340 (3')	Two	3748 in ²	50'

STANDARD REPLACEMENT COMPONENT PARTS

MODEL	CATALOG NUMBER	55-GALLON DRUM	LARGE POLY FILTER	SUPPORT RODS	4-WHEEL DOLLY	ADAPTER
SE JUMBO	95954	95942	90378 (1 req.)	98049 (1 Req.)	98088	90331
DE JUMBO	95960	95942	90378 (2 req.)	98049 (2 Req.)	98088	90332

OPTIONAL ITEMS AND ACCESSORIES FOR SINGLE ELECTRIC JUMBO

90637 includes the below items.

MUFFLER*	LIQUID SHUT-OFF FLOAT	1.5" WET/DRY ATTACHMENT SET W/STATIC HOSE	1.5" x 15' NEOPRENE HOSE	1.5" X 15' URETHANE STATIC CONDUCTIVE HOSE W/O SLEEVE	DOUBLE CURVED 1.5" WAND	14" X 1.5" SQUEEGEE FLOOR TOOL	14" X 1.5" FIBRE FLOOR TOOL	18" x 1.5" ROUND NOZZLE	1.5" HOSE ADAPTER
90447	90569	90637**	90191	90688	90286	90240	90242	90414	90331

OPTIONAL ITEMS AND ACCESSORIES FOR DUAL ELECTRIC JUMBO

90633 includes the below items.

MUFFLER*	LIQUID SHUT-OFF FLOAT 2 REQUIRED	2" WET/DRY ATTACHMENT SET W/POLY HOSE	2" x 15' NEOPRENE HOSE	2" X 10' POLY HOSE W/OUT SLEEVE***	2" DOUBLE CURVED WAND	12" X 2" FLOOR GULPER TOOL	22" X 2" SQUEEGEE FLOOR TOOL	18" X 2" ROUND NOZZLE	2" HOSE ADAPTER
90447	90569	90633**	90311	90312	90327	90320	90317	90444	90332

* Eliminates need for external filter in wet pick-up. Should not be used for dry recovery.

** Other attachment sets are also available in the Tornado Buyers Guide.

*** Please note: poly hoses are not oil resistant. When recovering oils, and additional Neoprene hose, which is oil and abrasive resistant, should be purchased.

Parish-Supply.com
Syracuse, NY 315-433-9031
www.parish-supply.com

