



Subhead Goes Here

From the innovative leader comes a carpet extractor with features, performance, and a price that are quite simply unsurpassed by the competition. This 20-gallon, self-propelled, forward-operation unit sets a new standard among self-contained carpet extractors. This rotationally-molded unit truly stands up to the rigors of daily use. Its 22" recovery shoe, 20-gallon solution tank, and 20-gallon recovery tank clean in the forward mode and handle large area extraction jobs with ease and efficiency.

Subhead Goes Here

The all new variable solution pump allows the operator to control the flow of solution to the carpet. Clean light or heavy soak, it's up to you. A 100 psi solution pump penetrates carpets deep-down and a three-stage vac motor with 135" waterlift ensures optimal cleaning performance. A sealed transaxle drive system, two large wheels, and twin front swivel casters provide easy transport over even the heaviest of carpet. The Marathon 2000 can cover up to 8,500 sq. ft. per hour, has variable, operator-controlled speed, and comes complete with a 22" vac shoe, pre-spray wand, and detachable 75-foot power cord.

Marathon 2000 Carpet Extractor

Rugged intelligent design, setting new standards for carpet extractors





Service-friendly

The Marathon 2000 is easily and quickly accessible for service and maintenance operations.

Professional design

A 22" vac shoe, easy-access drain hoses, and detachable 75-foot power cord are standard features on the Marathon 2000.



Quick-fill solution tank

The 20-gallon solution tank permits long periods of uninterrupted operation between refills.

Large-capacity recovery

A 20-gallon recovery tank has a clear cover for monitoring the tank level. The cover is sealed with a heavy-duty gasket for optimal recovery performance.



Built-in spray wand

The unit comes standard with a prespray hose and wand for handling edges, corners, and spotting operations.





High-performance carpet extraction

An adjustable brush, 100 psi solution pump, and 22" vac shoe provide deep-down cleaning in one pass.

Operator-friendly

A simple, easy-to-use control panel allows the operator to control speed, solution, and recovery functions. The handle continues Tornado's excellence in ergonomic design and commitment to operator comfort.



PRODUCT SPECIFICATIONS MODEL MARATHON 2000 PART NUMBER 98190 MACHINE DIMENSIONS DIMENSIONS (L X W X H) 51" x 22" x 38" NET WEIGHT 190 LBS SHIPPING WEIGHT SOLUTION TANK 20 GAL RECOVERY TANK 20 GAL DESIGN CHARACTERISTICS CORD 75 ft. Detachable CORD STRAIN RELIEF BODY CONSTRUCTION ROTATION ROTATION Polyethylene HANDLE MOIDE MOIDE MOIDE MELES TRANSPORT HANDLE WHEEL DIMENSIONS 6" Wheels DUMP SYSTEM	
PART NUMBER 98190 M A C H I N E D I M E N S I O N S DIMENSIONS (L X W X H) 51" x 22" x 38" NET WEIGHT 190 LBS SHIPPING WEIGHT SOLUTION TANK 20 GAL RECOVERY TANK 20 GAL DESIGN C H ARACTERISTICS CORD 75 ft. Detachable CORD STRAIN RELIEF BODY CONSTRUCTION ROTATION ROTATION Polyethylene HANDLE Molded Lift-Grip TRANSPORT HANDLE WHEEL DIMENSIONS 6" Wheels	
MACHINE DIMENSIONS DIMENSIONS (L X W X H) 51" x 22" x 38" NET WEIGHT 190 LBS SHIPPING WEIGHT SOLUTION TANK 20 GAL RECOVERY TANK 20 GAL DESIGN CHARACTERISTICS CORD 75 ft. Detachable CORD STRAIN RELIEF BODY CONSTRUCTION ROTATION Polyethylene HANDLE Molded Lift-Grip TRANSPORT HANDLE WHEEL DIMENSIONS 6" Wheels DUMP SYSTEM	ed
DIMENSIONS (L X W X H) S1" x 22" x 38" NET WEIGHT 190 LBS SHIPPING WEIGHT SOLUTION TANK 20 GAL RECOVERY TANK DESIGN CHARACTERISTICS CORD 75 ft. Detachable CORD STRAIN RELIEF BODY CONSTRUCTION Rotationally molde Polyethylene HANDLE Molded Lift-Grip TRANSPORT HANDLE WHEEL DIMENSIONS 6" Wheels	ed
NET WEIGHT SHIPPING WEIGHT SOLUTION TANK 20 GAL RECOVERY TANK 20 GAL DESIGN CHARACTERISTICS CORD 75 ft. Detachable CORD STRAIN RELIEF BODY CONSTRUCTION Rotationally molde Polyethylene HANDLE Molded Lift-Grip TRANSPORT HANDLE WHEEL DIMENSIONS 6" Wheels DUMP SYSTEM	ed
SHIPPING WEIGHT SOLUTION TANK 20 GAL RECOVERY TANK 20 GAL DESIGN CHARACTERISTICS CORD 75 ft. Detachable CORD STRAIN RELIEF BODY CONSTRUCTION HANDLE Molded Lift-Grip TRANSPORT HANDLE WHEEL DIMENSIONS 6" Wheels	ed
SOLUTION TANK 20 GAL RECOVERY TANK 20 GAL DESIGN CHARACTERISTICS CORD 75 ft. Detachable CORD STRAIN RELIEF BODY CONSTRUCTION HANDLE HANDLE TRANSPORT HANDLE WHEEL DIMENSIONS 6" Wheels DUMP SYSTEM	ed
RECOVERY TANK DESIGN CHARACTERISTICS CORD 75 ft. Detachable CORD STRAIN RELIEF BODY CONSTRUCTION Rotationally molde Polyethylene HANDLE Molded Lift-Grip TRANSPORT HANDLE WHEEL DIMENSIONS 6" Wheels DUMP SYSTEM	ed
DESIGN CHARACTERISTICS CORD 75 ft. Detachable CORD STRAIN RELIEF BODY CONSTRUCTION Rotationally molde Polyethylene HANDLE Molded Lift-Grip TRANSPORT HANDLE WHEEL DIMENSIONS 6" Wheels DUMP SYSTEM	ed
CORD 75 ft. Detachable CORD STRAIN RELIEF BODY CONSTRUCTION Rotationally molder Polyethylene HANDLE Molded Lift-Grip TRANSPORT HANDLE WHEEL DIMENSIONS 6" Wheels DUMP SYSTEM	ed
CORD STRAIN RELIEF BODY CONSTRUCTION Rotationally molds Polyethylene HANDLE Molded Lift-Grip TRANSPORT HANDLE WHEEL DIMENSIONS 6" Wheels DUMP SYSTEM	ed
BODY CONSTRUCTION Rotationally molder Polyethylene HANDLE Molded Lift-Grip TRANSPORT HANDLE WHEEL DIMENSIONS 6" Wheels DUMP SYSTEM	ed
HANDLE Molded Lift-Grip TRANSPORT HANDLE WHEEL DIMENSIONS 6" Wheels DUMP SYSTEM	ed
TRANSPORT HANDLE WHEEL DIMENSIONS 6" Wheels DUMP SYSTEM	
WHEEL DIMENSIONS 6" Wheels DUMP SYSTEM	
DUMP SYSTEM	
CLEANING CYCTEM	
CLEANING SYSTEM	
PRODUCTIVITY 3,200 - 8,500 sq. ft.	./hr.
CFM 95	
WATERLIFT 135"	
CLEANING PATH	
BRUSH SPEED	
BRUSH LENGTH 19"	
PSI 100	
SOUND LEVEL	
FILTRATION	
MOTORS	
VACUUM MOTOR 2 HP/3-stage	
WARRANTY	
LABOR 1 year	
PARTS 1 year	
REPLACEMENT ITEMS	
10" STANDARD WAND	
12" DELUXE WAND 98397	
20' VAC PRESSURE HOSE 95567	
STANDARD UTILITY TOOL 98340	
18" CREVICE DETAILER 98342	
4" UPHOLSTERY TOOL 98343	
6" UTILITY/STAIR TOOL 98344	
12/3 CORD 30713	

